0622

Frequency Drift in MR Spectroscopy: An 87-scanner 3T Phantom Study

Steve C.N. Hui^{1,2}, Mark Mikkelsen^{1,2}, Helge J. Zöllner^{1,2}, Vishwadeep Ahluwalia³, Sarael Alcauter⁴, Laima Baltusis⁵, Deborah A. Barany⁶, Laura R. Barlow⁷, Robert Becker⁸, Jeffrey I. Berman⁹, Adam Berrington¹⁰, Pallab K. Bhattacharyya^{1,1}, Jakob Uldby Blicher^{1,2}, Wolfgang Bogner^{1,3}, Mark S. Brown^{1,4}, Vince D. Calhoun¹⁵, Ryan Castillo¹⁶, Kim M. Cecil¹⁷, Yeo Bi Choi¹⁸, Winnie C.W. Chu¹⁹, William T. Clarke²⁰, Alexander R. Craven²¹, Koen Cuypers²², Michael Dacko²³, Zamilo de Ia Fuente-Sandoval²⁴, Patricia Desmond²⁵, Aleksandra Domagalik²⁶, Julien Dumont²⁷, Niall W. Duncan²⁸, Ulrike Dydak²⁹, Katherine Dyke³⁰, David A. Edmondson¹⁷, Gabriele Ende⁸, Lars Ersland³¹, C. John Evan³², Alan S. R. Fermin³³, Antonio Ferretti²⁴, Ariae Fillmer³⁵, Tao Gong³⁶, Ian Greenhouse³⁷, James T. Grist³⁸, Meng Gu³⁹, Ashley D. Harris³⁰, Katarzyan Hat⁴¹, Stefanie Heba⁴², Eva Heckova¹³, John P. Hegarty Il⁴³, Kirstin-Friederike Heise⁴⁴, Aaron Jacobson⁴⁵, Jacobson⁴⁵, Jacobson⁴⁵, Jacobson⁴⁵, Carbinson⁴⁵, Christopher W. Jenkins⁴⁷, Stephen J. Johnston⁴⁸, Christoph Juchem⁴⁹, Alayar Kangarlu⁵⁰, Adam B. Kerr⁵, Karl Landheer⁵¹, Thomas Lange⁵², Phil Lee³³, Swalt Rane Levendovszky⁵⁴, Catherine Limperopoulos⁵⁵ Feng Liu⁵⁶, William Iloyd⁵⁷, David J. Lythgoe⁵⁸, Maro G. Machizawa⁵⁹, Erin L. MacMillan⁷, Richard J. Maddock⁶⁰, Andrei V. Manzhurtsey⁵¹, Maria L. Martinez-Gudino⁶², Jack J. Miller⁶³, Heline Mirzakhanian⁶⁴, Paul G. Mullins⁶⁵, James Joseph Prisciandaro⁷³, Nick Puts⁵⁴, Caroline D. Rae⁵⁵, Francisco Reyes-Madrigal⁷⁶, Timothy P.L. Roberts⁹, Caroline D. Rae⁵⁷, Francisco Reyes-Madrigal⁷⁶, Timothy F.L.

Sones, "See Preut Manifeld Imaging Centre, School of Physics and Astronomy, University of Vaninghom, Natingham, United Magdom," Illinging Institute, The Celevant Class, Cleveland, Oil, United States, "Center of Functional Annual Neuroscience, America University, Medical Compus, Aurora, CO, United States," "Printatibilition Center for Transitional Research in Neuroscience Research, National Conference, and Compus, Aurora, CO, United States," "Printatibilitional Center for Transitional Research in Neuroscience Research Australia ("Programment of Imaging & Immerentian Indianal Center for Transitional Research International Center (Incinitate), Computer States, 1982, Computer States,

Synopsis

This project aimed to examine the relationship between gradient-induced heating and field drift on a large sample of MRI scanners. A standardized phantom protocol was established, and spectroscopy was performed before and after running 10 minutes of echo-planar imaging (EPI). MRS data were acquired from 87 scanners. The frequency drift trace was extracted by modeling the water signal in each transient. Drift rates of up to 1.3 Hz/minute were seen before EPI, and 4 Hz/minute after. This dataset will allow sites to benchmark scanner drift, for consideration in planning research protocol order and examine the need for real-time field-frequency locking.

Introduction

Heating of the gradient coils and thermal dissipation to the passive shims is a common cause of instability in the B_0 field, especially when echo-planar imaging (EPI) sequences are used (1-3). B_0 field drift changes the resonance frequency of spins, resulting in line broadening, decreased SNR and changes in editing efficiency for edited MRS experiments which rely on accurately placing frequency-selective pulses. To examine the extent and impact of gradient-induced frequency drift, a standardized protocol was distributed to sites with scanners from three vendors. By collecting data from a large number of sites, we aim to establish 'typical' levels of drift for benchmarking purposes, and to assess whether there is a widespread need for real-time field-frequency locking (2).

Methods

Phantom water signals were acquired with PRESS localization before and after a BOLD-weighted fMRI sequence. Standardized protocols were generated for GE, Philips and Siemens scanners consisting of: minimal preparatory imaging; pre-fMRI PRESS (TR/TE 5000/35 ms; 64 transients with data stored separately; no water suppression; voxel size 2 × 2 × 2 cm³, duration = 5:20 min); EPI BOLD sequence based on the ADNI-3 (4) protocol (TR/TE 3000/30 ms; 197 dynamics of one average; EPI factor 31, scan duration 10 min); and a long post-fMRI PRESS sequence (360 transients; other parameters same as pre-fMRI PRESS). Sites were instructed to use a water-dominant phantom of spherical or cylindrical shape. Phased-array head or head-and-neck coils with between 8 and 64 channels were used. Scanning was performed at least 6 hours after the previous scan to avoid any drift confounds due to heating effects. Phantoms were acclimatized in the scan room for the same period, and positioned at scanner isocenter. Spectral analysis was performed using MATLAB (R2020b, MathWorks, Natick, USA), including eddy-current correction, zero-filling and Fourier transformation. Frequency-domain pre- and post-fMRI PRESS spectra were modeled using a Lorentzian-Gaussian (Voigt) lineshape model to extract the water peak center frequency firm each individual transient. In order to compare frequency drift before and after EPI, the mean absolute frequency offset of the first 64 dynamics was calculated, and paired t-test was performed between pre- and post-fMRI PRESS. To visualize the effect of the observed frequency drifts on a typical 5-minute in vivo protocol, a simulated in vivo spectrum was generated using FID-A (5), including 18 major metabolites (TE = 35 ms; 2048 samples; 2 kHz spectral width, 2 Hz linewidth). The simulated spectrum was convolved with the frequency trace from the first 64 TRs of the phantom recording and spectra plotted. Fifty-eight sites repeated the acquisition protocol on a different day to allow investigation of the reproducibility of

Results

Data were received from 71 sites and 87 scanners (GE = 20, Philips = 28, Siemens = 39; 58 scanners submitted repeat data). Figure 1 shows the individual spectra for the highest-drifting scanner, before and after fMRI, with the frequency drift traces. Figure 2 shows the frequency drift traces overlaid for all 87 scanners. Scanners drifted by up to 7 Hz within 5 minutes before fMRI and by up to 26 Hz within 30 minutes after fMRI. Figure 3 shows a box plot of the absolute average frequency offset of each scanner (7). The mean absolute frequency offset across 64 transients (~5 min) was 0.78 ± 0.87 Hz (median = 0.4 Hz) and 1.33 ± 1.42 Hz (median = 0.8 Hz) respectively before and after fMRI. T-tests indicated drifting was significantly increased (p < 0.05) after fMRI, as expected. Simulated spectra that have been convolved with 64-transient water traces (the highest and lowest drift case for each vendor pre- and post-fMRI) are shown in Figure 4. The intensity of the NAA singlet is reduced by up to 26%, 44 % and 18% for GE, Philips and Siemens respectively, after fMRI. Since drift does not impact the noise, these peak signal losses represent predicted losses of SNR. Drift behavior was well correlated and reproducible. ICCs were 0.85 and 0.95 for pre- and post-fMRI PRESS repeated datasets, respectively. Pearson correlation coefficients (0.74 and 0.90) also showed good correlation between repeated datasets.

Discussion

Frequency drift data are presented for eighty-seven 3T MRI scanners. Median levels of drift were relatively low (5-minute average under 1 Hz), but the most extreme case suffered from higher levels of drift (up to 3.5 Hz before and 7.2 Hz after fMRI). These levels of drift lead to a measurable loss in SNR for short-TE MRS, as well as changes in editing efficiency and subtraction artefacts in edited MRS. Although the difference between pre- and post-fMRI was significant, it was lower than expected and there appears to be substantial drift associated with running scans 'from cold', as indicated by the pre-fMRI traces after only minimal preparatory imaging. Correlation analysis indicated that the drift was highly repeatable between sessions, so one might expect drift associated with previous scans within a protocol to be consistent.

Acknowledgements

This work was supported by NIH grants R01 EB016089, R01 EB023963, R21 AG060245, K99 EB028828 and K99 AG062230.

References

- 1. Foerster BU, Tomasi D, Caparelli EC. Magnetic field shift due to mechanical vibration in functional magnetic resonance imaging. Magn Reson Med 2005:54(5):1261-1267.
- 2. Henry PG, van de Moortele PF, Giacomini E, Nauerth A, Bloch G. Field-frequency locked in vivo proton MRS on a whole-body spectrometer. Magn Reson Med 1999;42(4):636-642.
- 3. Rowland BC, Liao H, Adan F, Mariano L, Irvine J, Lin AP. Correcting for Frequency Drift in Clinical Brain MR Spectroscopy. J Neuroimaging 2017;27(1):23-28.
- 4. Weiner MW, Veitch DP, Aisen PS, et al. The Alzheimer's Disease Neuroimaging Initiative 3: Continued innovation for clinical trial improvement. Alzheimers Dement 2017:13(5):561-571
- 5. Simpson R, Devenyi GA, Jezzard P, Hennessy TJ, Near J. Advanced processing and simulation of MRS data using the FID appliance (FID-A)-An open source, MATLAB-based toolkit. Magn Reson Med 2017;77(1):23-33.
- 6. R Core Team R: A Language and Environment for Statistical Computing, R Foundation for Statistical Computing, Vienna, Austria. 2020.
- 7. Zöllner HJ, Považan M, Hui SCN, Tapper S, Edden RAE, Oeltzschner G. Comparison of different linear-combination modelling algorithms for short-TE proton spectra. bioRxiv 2020:2020.2006.2005.136796.




Figure 1. Individual transients of pre- and post-fMRI PRESS (plotted in blue and red, respectively) from the highest-drifting scanner. The frequency offset derived from modeling the water signals is plotted (middle). 360 averages correspond to 30 minutes total scan duration.




Figure 2. Water offset traces of all 87 scanners. Pre- and post-fMRI traces are plotted in blue and red, respectively. 360 averages correspond to 30 minutes total scan duration.




Figure 3. Box plot for the mean absolute frequency offset for pre- and post-fMRI PRESS data on each scanner.




Figure 4. Comparison of simulated spectra with frequency drift applied between minimum and maximum drift for pre- and post-fMRI PRESS data. The minimum-drift case for each vendor (50% opacity) is overlaid with the maximum-drift case (opaque).

Proc. Intl. Soc. Mag. Reson. Med. 29 (2021) 0622